

Listing of Claims:

1. (currently amended) An adaptor for holding a surveillance camera inside a housing enclosure comprising a pair of complementary first and second interlocking shells for engagement around said camera, each such shell including a base, first and second sidewalls attached to said base, and an endwall attached to said base and extending between said sidewalls; said first shell having at least one locking tab on the outer edge of said first a sidewall thereof; and said second shell having at least one slot on the outer edge of said second a sidewall thereof such that the at least one tab of each of said first shell sidewalls engages the at least one slot of each of said second sidewalls of the complementary shell forming a single rectangular unit for holding around said camera.

2. (currently amended) The adaptor of claim 1 wherein a plurality of interior ridges are provided on ~~said~~ the base and ~~each of said~~ sidewalls of each of said shells forming a plurality of slots for holding PC boards associated with said camera.

3. (currently amended) The adaptor of claim 1 wherein a first outwardly
15 extending tab is provided on ~~said~~ the base of one of said shells at the corner where said base
meets ~~said~~ the first sidewall opposite from ~~said~~ the endwall, and a second outwardly extending
tab is provided on said base at the corner where said base meets ~~said~~ the second sidewall
opposite from ~~said~~ the endwall.

4. (currently amended) The adaptor of claim ~~[[3]]~~ 10 wherein at least one
20 mounting slot is provided in each of said outwardly extending tabs.

5. (currently amended) The adaptor of claim [[3]] 1 wherein at least one mounting opening is provided on the base of each at least one of said shells and on the first sidewall of each of said shells.

6. (currently amended) The adaptor of claim [[5]] 1 wherein an opening is
5 provided on each at least one of said endwalls for communication between the interior and exterior of said unit.

7. (currently amended) The adaptor of claim [[6]] 1 wherein at least one opening is provided on the base of each at least one of said shells for communication between the interior and exterior of said unit.

10 8. (currently amended) The adaptor of claim [[6]] 1 wherein at least one opening is provided on the first sidewall of each at least one of said shells for communication between the interior and exterior of said unit.

9. (currently amended) The adaptor of claim [[6]] 1 wherein at least one opening is provided on the second sidewall of each at least one of said shells for
15 communication between the interior and exterior of said unit.

10. (new) The adaptor of claim 3 wherein a third outwardly extending tab is provided on the base of the other of said shells at the corner where said base meets the first sidewall opposite from the endwall, and a fourth outwardly extending tab is provided on said base at the corner where said base meets the second sidewall opposite from the endwall.